



40-Year Paint Warranty

METAL PANELS INC. is pleased to present you with our 40-year limited paint warranty.

1. Our WeatherX™ Siliconized Polyester coil coatings, properly applied to HDG steel, (G90, G60) Galvalume, Zinc-Aluminum Alloy steel for commercial or industrial building parts will meet the following standards from the date of installation:

WILL NOT crack, chip or peel (lose adhesion) for forty (40) years. This does not include minute fracturing, which may occur in proper fabrication of the building parts. ***Failure due to substrate corrosion is excluded.***

SIDEWALL PANELS (for thirty (30) years from installation.

- a. WILL NOT chalk in excess of ASTM D-4214-98 method D659 number eight (8) rating.
- b. WILL NOT change color more than five (5.0) Hunter ΔE units as determined by ASTM method D-2244-02. Color change shall be measured on an exposed painted surface that has been cleaned of surface soils and chalk, and the corresponding values measured on the original or unexposed painted surface. It is understood that fading or color changes may not be uniform if the surfaces are not equally exposed to the sun and elements.

ROOFING PANELS (for thirty (30) years from installation.

- a. WILL NOT chalk in excess of ASTM D-4214-98 method A D659 number six (6) rating.
- b. WILL NOT change color more than (7.0) Hunter ΔE units as determined by ASTM method D-2244-02. Color change shall be measured on an exposed painted surface that has been cleaned of surface soils and chalk, and the corresponding values measured on the original or unexposed painted surface. It is understood that fading or color changes may not be uniform if the surfaces are not equally exposed to the sun and elements.

2. In case of a complaint, you will provide access to us and assist us as necessary in determining the exact cause of the failure. ASTM and NCCA testing procedures will be used.
3. If our WeatherX™ Siliconized Polyester family of coil coatings fail to comply with our limited Warranty, we will pay for labor and material reasonably necessary to repaint, repair or replace, at our option, the building part showing the failure. However, our liability shall not exceed the original purchased price of metal panels. In order for the warranty to be in effect, however, you must notify us in writing of the failure within thirty days of the discovery of such problem and provide documentation we may require. If we repaint, we will use normal painting practices using WeatherX™ Siliconized Polyester or other suitable alternatives. This Warranty also applies to the part we repainted, repaired, or replaced, but only for the unexpired portion of the Warranty period applicable to the original part.
4. Our LIMITED WARRANTY DOES NOT APPLY to circumstances which we do not control, including:
 - a. Fire or other casualty or physical damage;
 - b. Unusual harmful fumes or foreign substances in the atmosphere, standing water, or direct salt spray;
 - c. Damage due to abrasive or chemical cleaners;
 - d. Stored or installed in a way that allows for poor air circulation;
 - e. Stored or installed in a way that allows for contact with animals or animal waste;
 - f. Mishandled products, e.g., ANY PRODUCT THAT HAS BEEN ABUSED, ALTERED, MODIFIED, USING IN A MANNER NOT ORIGINALLY INTENDED, OR STORED CONTRARY TO OUR INSTRUCTIONS. Including a) damage to the product occasioned by condensation attributable to improper packaging, handling, shipping, processing, and/or installation; b) damage due to failure of the substrate.
5. This Warranty will apply only to metal, which is coated with WeatherX™ Siliconized Polyester and used on property located within the Continental United States.
6. We need to make clear that this is our only Warranty concerning these Siliconized Polyester coil coatings. And that we have no other obligations concerning them. So, please read and understand the following: Except for this Warranty, we make NO WARRANTY OR GUARANTEE EXPRESSED OR IMPLIED WITH RESPECT TO THE SILICONIZED POLYESTER COIL COATINGS. IMPLIED WARRANTIES OR FITNESS AND MERCHANTABILITY ARE EXCLUDED. Further, we have no other liability with respect to the Siliconized Polyester coatings, whether based on Warranty, negligence or any other legal theory. For example, we have no liability for consequential damages.
7. Metal Panels Inc. extends the Warranty solely to the Buyer. This is the complete Warranty of Metal Panels Inc. All of Metal Panels Inc. obligations to the Buyer are set forth and may not be altered unless done so in writing by Metal Panels Inc. This Warranty is non-transferable and non-assignable.

WARNING

AVOID DAMAGE

PROPER STORAGE

This material must be inspected immediately upon receipt and the presence of either moisture or white rust reported at that time. No claims for wet storage stain will be considered after 5 days from shipment.

Material must be kept warm and dry in inside storage only, where uniform temperature and good ventilation are available. Material should not be stored for prolonged periods in bundles as moisture may go undetected. If prolonged storage is necessary, the bundle should be broken and the sheets stored in an inclined position.

If outdoor storage cannot be avoided protect the metal with canvas or waterproof paper. Keep the sheets off the ground in an inclined position with an insulator such as wood. Under no circumstances is plastic to be used as it causes sweating and condensation.

CAUTION !!! Sharp edges, wear protective clothing and gloves.

METAL
PANELS
INC.