

FACED METAL BUILDING INSULATION BLANKET

Description

Guardian laminated metal building insulation is a high-quality fiberglass blanket used for metal building applications.

Guardian Faced Metal Building Insulation:

- Reduces Energy Costs
- Helps Control Condensation
- Improves Noise Control
- Provides Enhanced Light Reflectance
- Can Be Left Exposed**

The recovered R-values of all faced Guardian metal building insulation products are guaranteed at time of installation. For complete warranty details visit www.silvercote.com.

Available Products

R-Value	Nominal Thickness	Widths
R-8	2.5"	36", 48", 60", 72"
R-10	3"	36", 48", 60", 72"
R-11	3 1/2"	36", 48", 60", 72"
R-12	3 1/2"	36", 48", 60", 72"
R-13	4"	36", 48", 60", 72"
R-16	5"	36", 48", 60", 72"
R-19	6"	36", 48", 60", 72"
R-20	6"	36", 48", 60", 72"
R-21	6 3/4"	36", 48", 60", 72"
R-25	8"	36", 48", 60", 72"
R-28	8"	36", 48", 60", 72"
R-30	9 1/2"	36", 48", 60", 72"

For additional R-values and thicknesses call for quote. Non-standard widths may also be available.

Application

Laminated fiberglass insulation is a widely used form of insulation for metal buildings. Guardian laminated fiberglass insulation blanket is used in a variety of installation methods; however, it is typically installed between the structural steel and sheeting. Hot melt adhesive lamination provides a smoother finish, allowing blanket to be installed with appropriate droop, while still providing a clean interior appearance.

Technical Data

*Fire hazard Classification: (Composite test of fiberglass adhesive and facing)**	Flame Spread <25 Smoke Developed <50
Corrosion Resistance:	Will not accelerate corrosion of steel or copper.
Resistance To Fungi And Bacteria:	Does not breed or promote fungi or bacteria growth.
Odor:	Commercially odorless.

*The above flame spread rating was determined in accordance with ASTM E 84. This standard is used solely to measure and describe properties of materials and products in response to heat and flame under controlled laboratory conditions. This numerical flame spread is not intended to reflect hazards presented by this or any other material under actual fire conditions.

NOTE: Condensation blanket is NOT sold as a thermal barrier. The insulating value of the product is negligible and should NOT be utilized in conditioned or semi-conditioned buildings where thermal performance of any degree is required.

**Excludes white vinyl faced fiberglass.

Continued on back.

Compliance and Specification Data

ASTM E 84 - Surface Burning, ASTM C 167, ASTM C 991, ASTM C 553, ASTM C 665 Type II Class A, Type III Class A

Tolerances subject to normal manufacturing variations.

see us at
Sweets.com



GLS159 2/10

29200 Fountain Pkwy., Solon, Ohio 44139
800-231-6200 · Fax: 440-248-9182
www.silvercote.com

© 2010 Guardian Building Products